Serial No. 10/629,604

IN THE CLAIMS:

Docket No.: 1081.1176

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with <u>underlining</u> and deleted text with <u>strikethrough</u>. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please CANCEL claims 11, 31 and 50 and AMEND claims 10, 12, 13, 17, 18, 22, 29 and 32-49 in accordance with the following:

 (ORIGINAL) A terminal device having a power saving mode in which the terminal device works with less power consumption than in a normal mode, said terminal device comprising:

a first display section the display of which is turned off during the power saving mode and resumed when restored to the normal mode;

a storage section which stores at least one URL on a network;

a second display section which displays either the URL stored in the storage section or identification information corresponding to the URL at least during the power saving mode; and

an access processing section which executes access processing against the URL, or a URL corresponding to the identification information, displayed on the second display section in response to a cancellation operation of the power saving mode.

- (ORIGINAL) The terminal device according to claim 1, wherein, depending on a URL type, the access processing section activates an application program necessary for accessing the URL, and said application program makes access to the URL.
- 3. (ORIGINAL) The terminal device according to claim 2, wherein, when the URL type is a type designating a Web page address on the network, the access processing section activates a browser program, and

when the URL type is a type designating an electronic mail address, the access processing section activates a mail program.

4. (ORIGINAL) The terminal device according to claim 1, wherein the storage section stores a URL accessed last time before shifting to the power saving mode.

- 5. (ORIGINAL) The terminal device according to claim 1, wherein the storage section stores an arbitrary URL according to an instruction by a user.
 - 6. (ORIGINAL) The terminal device according to claim 1, wherein in the case the storage section stores a plurality of URLs, the terminal device

a first operation section for selecting a URL, or identification information corresponding to the URL, displayed on the second display section out of the plurality of URLs.

7. (ORIGINAL) The terminal device according to claim 1,

further comprises:

wherein the first display section is mounted so as to be opened and closed against a main body of the terminal device, and

the second display section is disposed in a visible position when the first display section is placed in a closed condition.

- 8. (ORIGINAL) The terminal device according to claim 7, further comprising: a second operation section for canceling the power saving mode, being disposed in an operable position while the first display section is placed in the closed condition.
- 9. (ORIGINAL) The terminal device according to claim 7, further comprising: a drive section which enables to open the first display section being closed in the power saving mode, in response to the cancellation operation of the power saving mode.
- 10. (CURRENTLY AMENDED) A device having a normal working state and a standby state, comprising:

a display section which can display information in the standby state; and

a processing section which performs processing corresponding to the information being displayed on the display section at the time of shifting from the standby state to the normal working state-;

a main display section the display contents of which are placed in a visible condition

during the normal working state, or placed in an invisible condition during the standby state; and

a detection section which detects an operation for shifting the display contents of the

main display section from the invisible condition to the visible condition, wherein:

the display section is a subordinate display section the display contents of which are placed in the visible condition even when said main display section is placed in the invisible condition, and

the processing section performs processing corresponding to the information displayed on the subordinate display section at the time of the detected operation.

11. (CANCELLED)

12. (CURRENTLY AMENDED) The device according to claim 4110,

wherein the normal working state is a normal working mode in which said main display section is placed in a display condition, and the standby state is a power saving mode in which said main display section is placed in a non-display condition and the device works with less power consumption than in the normal working mode, and the detection section detects a shift from the power saving mode to the normal working mode.

- 13. (CURRENTLY AMENDED) The device according to claim 4410, wherein a URL of a Web page is displayed on the subordinate display section, and when a state shift operation is detected by the detection section, the processing section displays on the main display section the Web page corresponding to the URL displayed on said subordinate display section.
- 14. (ORIGINAL) The device according to claim 13 further comprising: a registration section in which the URL displayed on the subordinate display section can be registered by a user.
- 15. (ORIGINAL) The device according to claim 13, wherein the URL displayed on the subordinate display section is a URL of a Web page the update of which is detected.
 - 16. (ORIGINAL) The device according to claim 15,

wherein the URL is a URL of the Web page the update of which is detected by patrolling the registered URL and determining an updated condition of each URL.

17. (ORIGINAL) The device according to claim 10,

wherein information related to voice data is displayed on the display section, and at the time of shifting from the standby state to the normal working state, based on the information displayed on the display section, the processing section performs regeneration of the voice data corresponding to said information.

18. (ORIGINAL) The device according to claim 10,

wherein information related to an electronic mail is displayed on the display section, and at the time of shifting from the standby state to the normal working state, based on the information displayed on the display section, the processing section performs processing related to the electronic mail corresponding to said information.

19. (ORIGINAL) The device according to claim 18, further comprising:

a main display section the display contents of which are placed in a visible condition in the normal working state, or in an invisible condition in the standby state,

wherein the display section is a subordinate display section the display contents of which are placed in the visible condition even when said main display section is placed in the invisible condition; and

a detection section which detects an operation for shifting the display contents of the main display section from the invisible condition to the visible condition,

wherein, based on the information displayed on the subordinate display section at the time of the detected operation, the processing section performs processing related to the electronic mail corresponding to said information.

20. (ORIGINAL) The device according to claim 19,

wherein information related to an electronic mail address is displayed on the subordinate display section, and

when a state shift operation is detected by the detection section, the processing section displays on the main display section a screen for creating an electronic mail addressed to the electronic mail address corresponding to the information displayed on the subordinate display section.

21. (ORIGINAL) The device according to claim 19,

wherein information related to a received electronic mail is displayed on the subordinate display section, and

when a state shift operation is detected by the detection section, the processing section displays on the main display section the received mail information corresponding to the information displayed on the subordinate display section.

22. (ORIGINAL) The device according to claim 10,

wherein information related to a telephone number is displayed on the display section, and

at the time of shifting from the standby state to the normal working state, based on the information related to the telephone number displayed on the display section, the processing section performs processing related to the corresponding telephone number.

23. (ORIGINAL) The device according to claim 22, further comprising: a telephone directory data in which a user can register a telephone number, wherein information related to the telephone number registered in the telephone directory data is displayed on the display section, and

the processing section originates a call by use of the telephone number.

24. (ORIGINAL) The device according to claim 22, further comprising: history information related to a telephone number, which is constituted of a call origination history and/or a call termination history,

wherein information related to the telephone number registered in the history information is displayed on the display section, and

the processing section originates a call by use of the telephone number.

25. (ORIGINAL) The device according to claim 22,

wherein information related to a telephone number of an originating party corresponding to a recorded voice data is displayed on the display section, and

the processing section regenerates the voice data corresponding to the information related to the telephone number.

Docket No.: 1081,1176

26. (ORIGINAL) The device according to claim 10,

wherein information related to an executable program is displayed on the display section, and

at the time of shifting from the standby state to the normal working state, based on the information displayed on the display section, the processing section executes the program corresponding to said information.

27. (ORIGINAL) The device according to claim 22, further comprising:

a main display section the display contents of which are placed in a visible condition in the normal working state, or placed in an invisible condition in the standby state; and

a detection section which detects an operation for shifting the display contents of the main display section from the invisible condition to the visible condition,

wherein the display section is a subordinate display section the display contents of which are placed in the visible condition even when said main display section is placed in the invisible condition, and

based on the information related to the telephone number displayed on the subordinate display section at the time of the detected operation, the processing section performs processing related to the telephone number corresponding to said information.

28. (ORIGINAL) The device according to claim 27, further comprising:
a telephone directory data in which a user can register a telephone number,
wherein information related to the telephone number registered in the telephone directory
data is displayed on the subordinate display section, and

when a state shift operation is detected by the detection section, the processing section displays on the main display section the telephone directory data contents corresponding to the information displayed on the subordinate display section, at least excluding the information displayed on the subordinate display section.

29. (CURRENTLY AMENDED) The device according to claim 4110, further comprising:

a folding mechanism by which the device can be opened and closed,

wherein the main display section is disposed in a position in which the display contents of the main display section are visible when the folding mechanism is placed in an open condition, while the display contents of the main display section are invisible when the folding mechanism is placed in a closed condition,

the display section is a subordinate display section disposed in a position in which the display contents of the subordinate display section are visible even when the folding mechanism is placed in the closed condition, and

the detection section detects an open motion of the folding mechanism from the close condition.

30. (CURRENTLY AMENDED) A <u>computer readable storage for controlling a</u>

<u>computer, comprising a program to be executed in a device by the computer having a normal working state, a standby state and a <u>subordinate</u> display section, said program comprising:

displaying information on the <u>subordinate</u> display section during the standby state; and</u>

at the time of shifting from the standby state to the normal working state, performing processing corresponding to information displayed on the <u>subordinate</u> display section, wherein:

the device includes a main display section, the display contents of which are placed in a visible condition in the normal working state, or placed in an invisible condition in the standby state, and

the display contents of the subordinate display section are placed in the visible condition even when said main display section is placed in the invisible condition; and said program further comprises:

detecting an operation for shifting the display contents of the main display section from the invisible condition to the visible condition; and

performing processing corresponding to the information displayed on the subordinate display section at the time of the detected operation.

- 31. (CANCELLED)
- 32. (CURRENTLY AMENDED) The program-computer readable storage according to claim 3430,

wherein the normal working state is a normal working mode in which said main display section is placed in a display condition, and the standby state is a power saving mode in which said main display section is placed in a non-display condition and the device works with less power consumption than in the normal working mode, and

said program further comprises:

detecting a shift operation from the power saving mode to the normal working mode.

33. (CURRENTLY AMENDED) The program-computer readable storage according to claim 3430, further comprising:

displaying a URL of a Web page on the subordinate display section; and on detection of a state shift operation, performing processing so that the Web page corresponding to the URL displayed on said subordinate display section is displayed on the main display section.

- 34. (CURRENTLY AMENDED) The program-computer readable storage according to claim 33, wherein the URL displayed on the subordinate display section is arbitrarily registered by a user.
- 35. (CURRENTLY AMENDED) The program-computer readable storage according to claim 33.

wherein the URL displayed on the subordinate display section is a URL of a Web page the update of which is detected.

36. (CURRENTLY AMENDED) The program-computer readable storage according to claim 33, further comprising:

determining an updated condition of each URL by patrolling the registered URL; and displaying on the subordinate display section the URL of the Web page the update of which is detected.

37. (CURRENTLY AMENDED) The program-computer readable storage according to claim 30, <u>said program further comprising</u>:

displaying information related to voice data on the display section; and at the time of shifting from the standby state to the normal working state, based on the information displayed on the display section, performing regeneration of the voice data corresponding to said information.

38. (CURRENTLY AMENDED) The program-computer readable storage according to claim 30, said program further comprising:

displaying information related to an electronic mail on the display section, and at the time of shifting from the standby state to the normal working state, based on the information displayed

on the display section, performing processing related to the electronic mail

Serial No. 10/629,604

Docket No.: 1081.1176 corresponding to said information.

39. (CURRENTLY AMENDED) The program-computer readable storage according to claim 38, wherein:

the device includes a main display section, the display contents of which are placed in a visible condition in the normal working state, or in an invisible condition in the standby state,

the display section is a subordinate display section, the display contents of which are placed in the visible condition even when said main display section is placed in the invisible condition, and

said program further comprises:

detecting an operation for shifting the display contents of the main display section from the invisible condition to the visible condition; and

at the time of the detected operation, performing processing related to the electronic mail corresponding to the information displayed on the subordinate display section.

40. (CURRENTLY AMENDED) The program-computer readable storage according to claim 39, said program further comprising:

displaying information related to an electronic mail address on the subordinate display section; and

on detection of the state shift operation, displaying on the main display section a screen for creating an

electronic mail addressed to the electronic mail address corresponding to the information displayed on the subordinate display section.

41. (CURRENTLY AMENDED) The program-computer readable storage according to claim 39, said program further 40 comprising:

displaying information related to a received electronic mail on the subordinate display section, and

on detection of the state shift operation, displaying on the main display section the received mail information

corresponding to the information displayed on the subordinate display section.

42. (CURRENTLY AMENDED) The program-computer readable storage according to claim 30, said program further comprising:

displaying information related to a telephone number on the display section, and at the time of shifting from the standby state to the normal working state, based on the information related to the telephone number displayed on the display section,

performing processing related to the telephone number corresponding to said information.

43. (CURRENTLY AMENDED) The program-computer readable storage according to claim 42, wherein the device includes a telephone directory data in which a user can register a telephone number, and said program further comprises:

displaying information related to the telephone number registered in the telephone directory data on the display section; and

at the time of shifting from the standby state to the normal working state, based on the information related to the telephone number displayed on the display section, originating a call by use of the telephone number corresponding to said information.

44. (CURRENTLY AMENDED) The program-computer readable storage according to claim 42, <u>said program further comprising</u>:

storing history information related to a telephone number constituted of a call origination history and/or a call termination history;

displaying information related to the telephone number registered in the history information is displayed on the display section; and

at the time of shifting from the standby state to the normal working state, based on the information related to the telephone number displayed on the display section, originating a call by use of the telephone number corresponding to said information.

45. (CURRENTLY AMENDED) The program-computer readable storage according to claim 42, <u>said program further comprising</u>:

displaying, on the display section, information related to a telephone number of an originating party corresponding to a recorded voice data; and

at the time of shifting from the standby state to the normal working state, based on the information related to the telephone number displayed on the display section, regenerating the voice data corresponding to the information related to the telephone number corresponding to said information.

Serial No. 10/629,604

Docket No.: 1081.1176

46. (CURRENTLY AMENDED) The program-computer readable storage according to claim 30, <u>said program further comprising</u>:

displaying information related to an executable program on the display section; and at the time of shifting from the standby state to the normal working state, based on the information displayed on the display section, executing a program corresponding to said information.

47. (CURRENTLY AMENDED) The program-computer readable storage according to claim 42, wherein:

the device includes a main display section the display contents of which are placed in a visible condition in the normal working state, or in an invisible condition in the standby state,

the display section is a subordinate display section the display contents of which are placed in the visible condition even when said main display section is placed in the invisible condition, and

said program further comprises:

detecting an operation for shifting the display contents of the main display section from the invisible condition to the visible condition; and

based on the information related to the telephone number which is displayed on the subordinate display section at the time of the detected operation, performing processing related to the telephone number corresponding to said information.

48. (CURRENTLY AMENDED) The program-computer readable storage according to claim 47, wherein:

the device includes a telephone directory data in which a user can register a telephone number, and said program further comprises:

displaying information related to the telephone number registered in the telephone directory data on the subordinate display section; and

on detection of a state shift operation, displaying on the main display section the telephone directory data contents corresponding to the information displayed on the subordinate display section, at least excluding the information displayed on the subordinate display section.

12

49. (CURRENTLY AMENDED) The program-computer readable storage according to claim 3130, wherein:

the device includes a folding mechanism by which the device can be opened and closed, the main display section is disposed in a position in which the display contents of the main display section are visible when the folding mechanism is placed in an open condition, and the display contents of the main display section are invisible when the folding mechanism is placed in a closed condition, and

the display section is a subordinate display section disposed in a position in which the display contents of the subordinate display section are visible even when the folding mechanism is placed in the closed condition,

said program further comprising:

detecting an open motion of the folding mechanism from the closed condition as the shift operation.

- 50. (CANCELLED)
- 51. (PREVIOUSLY PRESENTED) A device having a standby state, comprising:
 a display displaying information during the standby state; and
 a processor executing processing corresponding to the information displayed at the time
 of shifting from the standby state.
- 52. (PREVIOUSLY PRESENTED) The device according to claim 51, wherein the shifting from the standby state comprises canceling the standby state.
- 53. (PREVIOUSLY PRESENTED) The device according to claim 51, wherein the shifting from the standby state comprises shifting to a normal working state.
- 54. (PREVIOUSLY PRESENTED) The device according to claim 51, wherein the standby state is a power saving mode.